

(512) 444-7938



(512) 440-8029

6511 MANCHACA ROAD • AUSTIN, TEXAS 78745

ACRYLIC-IMPREGNATED FINISHES

As with any flooring product, follow a program of cleaning, sweeping and vacuuming to eliminate as much dirt and grit as possible, and remember that moisture should not come in contact with the floor. If it does, it should be wiped up immediately. A good quality dust mop is great for quick clean up and for heavy traffic areas. Vacuum your wood floors at the same time you vacuum your carpets. The beater bars on a vacuum should not be used.

Always use the manufacturers recommended cleaning product if possible.

Warranties will be voided by using oil soap cleaners or oil based cleaners.

Use a low-speed buffer using cleaning products recommended by the wood manufacturer. If more than one step in cleaning is required you may have to use different pads for each step.

Use recommended dust mop treatments to enhance dust mopping.

For white/bleached products use an untreated dust mop. Never use water or petroleum based products. These white floors usually use a special cleaning product that is applied with a buffer.

If floor is dull it may require screening followed by the recommended products.

Stubborn dirty spots may be cleaned with the proper products, but may require spot sanding.

This is very generic because the manufactures of these products require very specific products to clean their floors. These products do not cross over to other products very well. It is important to know what company made your wood flooring to obtain the proper cleaning products.